

KRYTEX MOTO

Composite protective coating for motorcycles

Packaging: 50 ml

A composite protective coating for motorcycles: adds gloss and color depth to painted parts and makes the surface slicker; also suitable for vinyl and plastic.



KEY PROPERTIES

- Makes the surface slicker.
- Reduces dirt build-up and makes cleaning easier.
- Suitable for vinyl and plastic parts.
- Protects painted parts from UV.
- Lowers the risk of damage from harsh car-wash chemicals and unskilled staff.
- Boosts gloss, depth and color richness of painted parts.

SPECIFICATIONS

Contact angle	115°
Service life	up to 6 months
Consumption	3–4 ml/m ²

Application	Motorcycles
Cure before delivery	≥ 6–8 h
Volume	50 ml

HOW TO APPLY

- 01** Two-phase wash; remove tar, oil stains and iron fallout, then clay the paint to lift remaining contamination.
- 02** Polish the paint.
- 03** Degrease thoroughly with KRYTEX DEGREASER.
- 04** Load the applicator with 10–15 drops; add 3–5 drops as you go.
- 05** Apply in small sections, cross-hatch.
- 06** Within 10 s, when the coating starts to bead, buff to a gloss with a clean dry microfiber using moderate pressure.
- 07** Overlap the next section and buff the overlap carefully.
- 08** Cure at least 6–8 h before handing the motorcycle over.
- 09** Work at 15–25 °C and humidity no higher than 60%, out of direct sunlight and away from water.

COMPOSITION & STORAGE

Composition	Alkane solvent, fluorinated hydrocarbons, trimethylated silica, aminosilicone, polyorganosiloxane, tetraethoxysilane.
Shelf life	60 months
Storage	Keep tightly closed in the original container in a dry place at 0...+25 °C, away from direct sunlight. Do not use after the expiry date.