

KRYTEX PPF SOAP

Concentrated film installation soap

Packaging: 100 ml / 500 ml

Enough for: 500 ml ≈ 15–20 cars

A pH-neutral concentrate for installing polyurethane, tint and architectural films. Its formula creates a soap membrane that makes positioning the film easy and comfortable. Dilute with water 1:200–1:600; 500 ml covers about 15–20 cars.



KEY PROPERTIES

- For installing polyurethane PPF, window tint and architectural films.
- Creates a slip layer for controlled film positioning.
- pH-neutral formula.
- Dilute with water 1:200–1:600.

SPECIFICATIONS

Type	Concentrate	Dilution	1:200–1:600 with water
Application	Installing polyurethane, tint and architectural films	Volume	100 ml / 500 ml
pH	neutral	Enough for	500 ml ≈ 15–20 cars

COMPOSITION & STORAGE

Composition	Anionic surfactants, amphoteric surfactants, polyglycosides, propylene glycol, isopropyl alcohol, non-ionic surfactants, distilled water, preservatives, fragrance.
Shelf life	36 months
Storage	Keep tightly closed in the original container at +5...+25 °C. Do not freeze. Do not use after the expiry date.
Precautions	In case of contact with skin or mucous membranes, rinse with plenty of water; seek medical advice if needed. Keep away from children.